



ValueJet VJ-1938TX



- Made in Japan
- 1910 mm Width
- Dual Head Setup
- Head Height up to 6 mm
- Up to 1440 dpi

75" (191 cm) Wide Direct-to-Textile Printer

ValueJet 1938TX is Mutoh's new generation digital piezo drop-on-demand direct-to-textile printer combining proven technology with a high-precision mechanical design. Developed in Japan, the 75" (1910 mm) wide VJ-1938TX can print directly on a wide range of fabrics up to a thickness of 3.5 mm. The printer will deliver quality production speeds up to 40 m²/h.

The 1938TX can print on closed, open non-stretch and two way stretch fabrics thanks to the incorporated ink gutter and a newly engineered high-end fabric feeding, tensioning and take-up system which will guarantee worry-free feeding and transport of fabrics. The preferred solution for garment printing professionals!

Product Highlights

- Dual staggered head design with latest drop-on-demand piezo inkjet technology.
- Variable drop printing - wide range of droplets & three drop families. Small droplets ideal for light fabrics. Larger droplets ideal for thicker fabrics requiring higher ink loads.
- Head height up to 6 mm to accommodate a wide range of fabrics.
- Typical high quality production speeds up to 40 m²/h.
- Newly engineered high end fabric feeding, front & back tensioning and motorised take-up system for media weights up to 100 kg.
- Integrated gutter system for open textiles.

Application Possibilities

The ValueJet 1938TX is specifically targeted at sampling of short run on-demand & local digital production of garments, upholstery, fashion, swimwear, interior deco fabrics, home textiles, flags, etc..



Direct Textile



75" (191 cm) Wide Direct-to-Textile Printer

SPECIFICATIONS

Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	2 (staggered setup)
Nozzle Configuration	180 nozzles x 8 lines / head
Head Heights (mm)	Low: 2.5 mm / Middle: 3.5 mm / High: 6.0 mm

Power Consumption

During Printing	≤ 150 W
Off / Stand-by	≤ 1 W / ≤ 25W
Supply Voltage/Frequency	AC 100-240 V / 60 or 50 Hz

Media Specifications

Max. Media Width	1910 mm (75,19")
Max. Print Width	1900 mm (74,80")
Max. Media Thickness	1.2 - 2.3 - 3.5 mm *

* : Max. media thickness is specified per head height

Media Measurements *	Ø 250 mm / 50.8 mm or 2" & 75.2 mm or 3" / 100 kg
----------------------	---

* : Max. diameter / Core diameter compatibility / Max. mass

Fabric Winding	Supports both face-in & face-out rolled fabrics
----------------	---

Recommended Working Environment

Temperature	22 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation) with ΔRH: max. 5% RH/h

Machine Measurements

Width x Depth x Height	2983 x 1134 x 1261 mm
Weight	304 kg

Ink Type: Water-based Pigmented Direct Textile

Features	OEKO-TEX® Standard 100 product class I compliant Green solution using only heat fixation. No water required for post treatment (e.g. washing, steaming)
Fabric Compatibility	Cotton, silk, rayon, mixed fibre, PES
Ink Volume / Colours	1000 ml bags* / CMYK

* : 1000 ml bag requires optional adapter

Ink Type: Water-based Universal Sublimation inks (DS2-series)

Features	Transfer printing and direct printing. Excellent light, washing and perspiration fastness properties (ISO 105-B02, ISO 105-C02, ISO 105-E04) OEKO-TEX® Standard 100 compliant
Fabric Compatibility	Polyester and mixed fibre (min 80 % PES)
Ink Volume / Colours	1000 ml bottles / CMYK

Ink Type: Water-based Disperse Direct (DD-series)

Features	Inks for direct printing onto synthetic fibre. High outdoor light, 40°C soap wash, perspiration and rubbing fastness (ISO 105-B02, ISO 105-C02, ISO 105-E04) OEKO-TEX® Standard 100 compliant
Fabric Compatibility	Polyester
Ink Volume / Colours	1000 ml bottles / CMYK

Fabric Handling

The VJ-1938TX comes standard with a motorised unwinder/winder system. Perfect fabric transport is ensured by a sensor driven front and back tensioning system, allowing perfect roll preparation for after treatment on a calendar, fixation unit, wash or even steam unit, depending on the chosen ink chemistry. To handle different roll widths, the front and back core fixation flanges can be quickly and easily slid into position. Thanks to the head height range between 2.5 mm and 6 mm, the operator can load both short and long fibre fabrics, without having to worry about print head perturbation. A textile tensioning cylinder close to the print zone ensures that the fabric is kept under equal tension over the full printer width during printing.

